

## SAFETY DATA SHEET

---

### 1. IDENTIFICATION

**Product Name:** DAPCO™ 2100 Primerless Firewall Sealant, Form A (mixed)  
**Product Description:** Modified silicone resin  
**Synonyms:** None  
**Chemical Family:** Modified silicone resin  
**Molecular Formula:** Mixture  
**Molecular Weight:** Mixture  
**Intended/Recommended Use:** Engineered material sealant

CYTEC INDUSTRIES INC., FIVE GARRET MOUNTAIN PLAZA, WOODLAND PARK, NEW JERSEY 07424, USA  
**For Product and all Non-Emergency Information call 1-800/652-6013.** Outside the USA and Canada call 1-973/357-3193.

**EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:**

**Asia Pacific:**

Australia - +61-3-9663-2130 or 1800-033-111 (IXOM)  
China (PRC) - +86 0532 83889090 (NRCC)  
New Guinea - +61-3-9663-2130 or 1800-033-111  
New Zealand - +61-3-9663-2130 or 0800-734-607 (IXOM)  
India, Japan, Korea, Malaysia, Thailand - +65 3158 1074 (Carechem24 Singapore)  
India (Hindi Speaking Only) - +65 3158 1198 or 000800 100 7479 (Carechem24 Singapore)

**Canada:** +1-905-356-8310 (Cytec Welland, Canada plant)

**Europe/Africa/Middle East (Carechem24 UK):**

Europe, Middle East, Africa, Israel - +44 (0) 1235 239 670  
(Arabic speaking countries) - +44 (0) 1235 239 671

**Latin America:**

Brazil - 0800 7077 022 (SUATRANS)  
Chile - +56-2-2-247-3600 (CITUC QUIMICO)  
All Others - +52-376-73 74122 (Cytec Atequiza, Mexico plant)

**USA:** +1-703-527-3887 or 1-800-424-9300 (CHEMTREC #CCN6083)

The ® indicates a Registered Trademark in the United States and the ™ indicates a trademark in the United States. The mark may also be registered, subject of an application for registration, or a trademark in other countries.

---

### 2. HAZARDS IDENTIFICATION

**GHS Classification**

Skin Corrosion / Irritation Hazard Category 2  
Serious Eye Damage / Eye Irritation Hazard Category 1

**LABEL ELEMENTS**



**Signal Word**  
Danger

**Hazard Statements**

Causes skin irritation  
Causes serious eye damage

**Precautionary Statements**

Wash face, hands and any exposed skin thoroughly after handling.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF ON SKIN: Wash with plenty of soap and water.  
Specific treatment (see supplemental first aid instructions on this label).  
Take off all contaminated clothing and wash it before reuse.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER or doctor/physician.

**Hazards Not Otherwise Classified (HNOC), Other Hazards**

Use mechanical exhaust ventilation when heat-curing material.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance, Mixture or Article? Mixture

**HAZARDOUS INGREDIENTS**

Component / CAS No.	%	GHS Classification	Carcinogen
Calcium carbonate 471-34-1	38 - 42	Eye Dam. 1 (H318) Skin Irrit. 2 (H315)	-
Titanium Dioxide 13463-67-7	1 - 2	Aquatic Acute 3 (H402) Aquatic Chronic 3 (H412)	IARC 2B
Trimethylated silica 68909-20-6	1 - 1.5	Not Classified	-
Triiron tetraoxide 1317-61-9	0.5 - 1.5	Not Classified	-
glass, oxide, chemicals 65997-17-3	0.5 - 1.5	Not Classified	-
Carbon Fiber 7440-44-0	0.5 - 1.5	Not Classified	-

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

---

**4. FIRST AID MEASURES**

**DESCRIPTION OF FIRST AID MEASURES**

**Eye Contact:**

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical attention immediately.

**Skin Contact:**

Wash immediately with plenty of water and soap. Remove contaminated clothing and shoes without delay. Obtain medical attention. Do not reuse contaminated clothing without laundering. Destroy or thoroughly clean shoes before reuse.

**Ingestion:**

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

**Inhalation:**

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms.

**MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED**

None known

**INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDS**

**Notes To Physician:**

Formaldehyde is not a component of this product, however, heating to temperatures above 150 C in the presence of air may result in the release of formaldehyde. The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen. Formaldehyde is irritating to the eyes, nose, throat and skin and is a dermal sensitizer.

---

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media:**

Use water spray or fog, carbon dioxide or dry chemical.

**Extinguishing Media to Avoid:**

full water jet

**Protective Equipment:**

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See MSDS Section 8 (Exposure Controls/Personal Protection).

**Special Hazards:**

Keep containers cool by spraying with water if exposed to fire.

---

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:**

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. Refer to Section 8 (Exposure Controls/Personal Protection) for appropriate personal protective equipment.

**Methods For Cleaning Up:**

Sweep up into containers for disposal. Flush spill area with water.

**References to other sections:**

See Sections 8 and 13 for additional information.

---

## 7. HANDLING AND STORAGE

### HANDLING

## 7. HANDLING AND STORAGE

**Precautions:** Wash hands thoroughly after handling. Wear protective gloves and eye/face protection.

**Special Handling Statements:** Heating to temperatures above 150 C (302 F) in the presence of air may result in the release of formaldehyde. Formaldehyde is a known animal carcinogen and is considered to be probably carcinogenic to humans by the International Agency for Research on Cancer and the National Toxicology Program. Formaldehyde is irritating to the eyes, nose, throat and skin and is a dermal sensitizer. The permissible exposure limit for formaldehyde should not be exceeded. Provide good ventilation of working area (local exhaust ventilation if necessary).

### STORAGE

Store in accordance with local, state, and federal regulations.

**Storage Temperature:** Store at <27 °C 80 °F

**Reason:** Quality.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering Measures:

Utilize a closed system process where feasible. Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure when spraying or curing at elevated temperatures.

### Respiratory Protection:

Where exposures are below the established exposure limit, no respiratory protection is required. Where exposures exceed the established exposure limit, use respiratory protection recommended for the material and level of exposure.

### Eye Protection:

Prevent eye and skin contact. Provide eye wash fountain and safety shower in close proximity to points of potential exposure. Wear eye/face protection such as chemical splash proof goggles or face shield.

### Skin Protection:

Prevent contamination of skin or clothing when removing protective equipment. Barrier creams may be used in conjunction with the gloves to provide additional skin protection. Wear impermeable gloves and suitable protective clothing.

### Hand Protection:

Wear impermeable gloves. Replace gloves immediately when torn or any change in appearance (dimension, colour, flexibility etc) is noticed. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

### Additional Advice:

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water.

---

### Exposure Limit(s)

The below constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### 13463-67-7 Titanium Dioxide

OSHA (PEL): 15 mg/m<sup>3</sup> total dust (TWA)

ACGIH (TLV): 10 mg/m<sup>3</sup> (TWA)

Other Value: Not established

#### 471-34-1 Calcium carbonate

OSHA (PEL): 15 mg/m<sup>3</sup> total dust (TWA)

5 mg/m<sup>3</sup> respirable fraction (TWA)

**13463-67-7 Titanium Dioxide**

ACGIH (TLV): Not established  
Other Value: Not established

**65997-17-3 glass, oxide, chemicals**

OSHA (PEL): Not established  
ACGIH (TLV): 1 f/cc respirable fibers (TWA)  
5 mg/m<sup>3</sup> inhalable fraction (TWA)  
Other Value: Not established

**68909-20-6 Trimethylated silica**

OSHA (PEL): 5 mg/m<sup>3</sup> ceiling (Dow Corning)  
ACGIH (TLV): Not established  
Other Value: 5 mg/m<sup>3</sup> ceiling (Dow Corning)

**7440-44-0 Carbon Fiber**

OSHA (PEL): Not established  
ACGIH (TLV): Not established  
Other Value: 3 fibers/cc (Cytec)

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Color:** blue  
**Appearance:** paste  
**Odor:** mild  
**Boiling Point:** Not applicable  
**Melting Point:** Not applicable  
**Vapor Pressure:** Not available  
**Specific Gravity/Density:** 1.45  
**Vapor Density:** Not applicable  
**Percent Volatile (% by wt.):** Not available  
**pH:** Not applicable  
**Saturation In Air (% By Vol.):** Not applicable  
**Evaporation Rate:** Not applicable  
**Solubility In Water:** Reacts with water  
**Volatile Organic Content:** Not available  
**Flash Point:** Not applicable  
**Flammability (solid, gas):** Not available  
**Flammable Limits (% By Vol):** Not applicable  
**Autoignition (Self) Temperature:** Not applicable  
**Decomposition Temperature:** Not applicable  
**Partition coefficient (n-octanol/water):** Not applicable  
**Odor Threshold:** Not available  
**Viscosity (Kinematic):** Not applicable

### DUST HAZARD INFORMATION

**Particle Size (microns):** Not available  
**Kst (bar-m/sec):** Not available  
**Maximum Explosion Pressure (Pmax):** Not available  
**Dust Class:** Not available  
**Minimum Ignition Energy (MIE) (mJ):** Not available  
**Minimum Ignition Temperature (MIT) (°C):** Not available  
**Minimum Explosive Concentration (MEC) (g/m<sup>3</sup>):** Not available  
**Limiting Oxygen Concentration (LOC) (%):** Not available

---

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Conditions To Avoid:</b>	None known
<b>Polymerization:</b>	Will not occur
<b>Conditions To Avoid:</b>	None known
<b>Materials To Avoid:</b>	Oxidizing agents Acids
<b>Hazardous Decomposition Products:</b>	oxides of carbon When heated to decomposition, it emits toxic fumes. calcium oxide

---

## 11. TOXICOLOGICAL INFORMATION

### PRODUCT TOXICITY INFORMATION

**Likely Routes of Exposure:** Oral, Skin, Eyes, Respiratory System.

#### ACUTE TOXICITY DATA

oral	rat	Acute LD50	>2000 mg/kg
dermal	rabbit	Acute LD50	>2000 mg/kg
inhalation	rat	Acute LC50 4 hr	>5 mg/l (Dust/Mist)

#### LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation	skin	Irritating
Acute Irritation	eye	Causes serious damage

#### ALLERGIC SENSITIZATION

Sensitization	skin	Not sensitizing
Sensitization	respiratory	No data

#### GENOTOXICITY

##### Assays for Gene Mutations

Ames Salmonella Assay	No data
-----------------------	---------

#### OTHER INFORMATION

The product toxicity information above has been estimated.

#### HAZARDOUS INGREDIENT TOXICITY DATA

Calcium carbonate has an acute oral (rat) LD50 of 6.5 g/kg. Direct contact will cause moderate skin and severe eye irritation. Inhalation of dust can cause mild respiratory irritation.

Acute exposure to titanium dioxide dust is not likely to cause adverse effects. Chronic exposure to titanium dioxide may cause some lung fibrosis. Inhalation of titanium dioxide dust at 50 times the nuisance dust level caused lung fibrosis and a slight increase in lung tumor incidence in laboratory rats. When titanium dioxide was fed to rats and mice over lifetime in a carcinogen bioassay, it was not carcinogenic.

Trimethylated silica, which is a unique form of fumed silica, is not expected to cause adverse health effects via inhalation, oral or dermal routes of exposure. Trimethylated silica does not cause the lung diseases crystalline silica is known to cause. The acute oral (rat) LD50 for fumed silica is 3.1 g/kg.

Triiron tetraoxide has an acute oral (rat) LD50 value of >5000 mg/kg. Inhalation of triiron tetraoxide fume or dust can deposit or collect in the lungs (siderosis) with little or no physical disability. Direct contact with this material may cause minimal-mild eye but no skin irritation is expected. Contact with this substance is not expected to produce dermal sensitization. In a subchronic oral toxicity study, Triiron tetraoxide was administered via nose-only inhalation to rats (20 animals/sex/dose) at concentration levels of 0, 4.7, 16.6 or 52.1 mg/m<sup>3</sup> for a period of 13 weeks. The No Observable Adverse Effect Level (NOAEL) was established at 4.7 mg/m<sup>3</sup>. There was no evidence for a carcinogenic potential in rats. Triiron tetraoxide was not mutagenic in the Ames assay or the in vitro mammalian cell gene mutation assay (CHO/HGPRT) and was not clastogenic in the in vitro Chromosomal Aberrations Assay.

Glass oxide is considered a nuisance particulate which will not cause adverse health effects other than respiratory congestion or irritation.

Carbon fibers may cause mechanical irritation of the eyes, skin, nose and throat. Airborne carbon fibers are not considered respirable. A typical carbon fiber may be characterized as having a diameter of 5-7 microns and a length greater than 100 microns. Fibers with diameters greater than 3.5 microns are not considered respirable.

California Proposition 65 Warning (applicable in California only) - This product contains (a) chemical(s) known to the State of California to cause cancer.

---

## 12. ECOLOGICAL INFORMATION

### TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

This material is not classified as dangerous for the environment.  
The ecological assessment for this material is based on an evaluation of its components.

### RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

### HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Algae	Toxicity to Fish	Toxicity to Water Flea
Calcium carbonate 471-34-1	Not available	Not available	Not available
Titanium Dioxide 13463-67-7	Not available	Not available	Not available
Trimethylated silica 68909-20-6	Not available	Not available	Not available

Component / CAS No.	Toxicity to Algae	Toxicity to Fish	Toxicity to Water Flea
Triiron tetraoxide 1317-61-9	Not available	Not available	Not available
glass, oxide, chemicals 65997-17-3	Not available	Not available	Not available
Carbon Fiber 7440-44-0	Not available	Not available	Not available

---

## 13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this MSDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this MSDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

---

## 14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

### US DOT

Dangerous Goods? Not applicable/Not regulated

### TRANSPORT CANADA

Dangerous Goods? Not applicable/Not regulated

### ICAO / IATA

Dangerous Goods? Not applicable/Not regulated

### IMO

Dangerous Goods? Not applicable/Not regulated

---

## 15. REGULATORY INFORMATION

### Inventory Information

**United States (USA):** All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.



**Canada:** All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

**European Economic Area (including EU):** Cytec has appointed an Only Representative to relieve our customers from their registration requirements under the REACH Regulation (EC) No. 1907/2006. Please contact us if you wish to benefit from the OR arrangement.

**Australia:** All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on AICS.

**China:** All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

**Japan:** All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese inventory.

**Korea:** All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory.

**Philippines:** All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine inventory.

**Switzerland:** All components of this product are exempt from the new substance notification requirements for Switzerland (SR 813.11 art. 16-17).

**Taiwan:** All components of this product are included on the Taiwan Chemical Substance Inventory (TCSI) or are not required to be listed on the Taiwan inventory.

#### **OTHER ENVIRONMENTAL INFORMATION**

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

#### **PRODUCT HAZARD CLASSIFICATION UNDER SECTION 311 OF SARA**

- Acute

---

## **16. OTHER INFORMATION**

### **NFPA Hazard Rating (National Fire Protection Association)**

Health: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 0 - Materials that in themselves are normally stable, even under fire exposure conditions.

**Reasons For Issue:** Revised Section 9

**Date Prepared:** 02/19/2016

**Date of last significant revision:** 02/16/2016

### **Component Hazard Phrases**

Calcium carbonate

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

Titanium Dioxide

H412 - Harmful to aquatic life with long lasting effects.

---

Prepared By: Legal & Compliance Services; E-mail: [custinfo@cytec.com](mailto:custinfo@cytec.com)

---

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.

---